11DoF inertial system for dynamics analysis of moving objects

Rosen Miletiev¹, Emil Iontchev², Ivaylo Simeonov³, Rumen Yordanov⁴

Abstract - The current paper proposed 11 DoF system based on 3-axis accelerometer, 3-axis gyroscope, 3-axis magnetometer, barometer and GPS receiver to calculate the dynamic response of the moving device and to solve the navigation tasks by combination of the IMU and GPS systems. Also GSM/GPRS modem is built-in to send the inertial and navigation data via GPRS connection to remote server to meet the real-time requirements. The experimental data are accomplished to represent the system possibilities to read, store and send the inertial and navigation data.

Keywords - inertial navigation, IMU system

I. INTRODUCTION

The dynamics analysis and localization of the moving objects define the necessity of the information and communication system with maximum number of degrees of freedom. MEMS technology allows production of small, cheap and low power consumption devices which may measure the linear and angular accelerations and may be used in different commercial applications [1]. Unfortunately the low-cost MEMS devices need of algorithms for compensation of their disadvantages, such as GPS-IMU system integration [2] to reduce the numerical integration errors, barometer – accelerometer combination [3] to reduce the dependency of the accelerometer data over the inclination or combined algorithms for calculation of the heading angle in the compass system [4].

The current paper proposed 11 DoF system based on 3-axis accelerometer, 3-axis gyroscope, 3-axis magnetometer, barometer and GPS receiver to calculate the dynamic response of the moving device and to solve the navigation tasks by combination of the IMU and GPS systems. The existing IMU measurement systems are combined only with a GPS receiver [5] and some of them also have build-in GSM modem, but the sampling frequency is much lower [6]. The sampling frequency in these systems varies from 20Hz [5] to 84Hz [7] while the proposed system read the inertial and navigation data

¹Rosen Miletiev is with the Faculty of Telecommunications at Technical University of Sofia, 8 Kl. Ohridski Blvd, Sofia 1000, Bulgaria. E-mail: <u>miletiev@tu-sofia.bg</u>

²Emil Iontchev is with the Higher School of Transport "T. Kableshkov" 158 Geo Milev Street, Sofia 1574, Bulgaria, E-mail: <u>e_iontchev@yahoo.com</u>

³Ivaylo Simeonov is with the Faculty of Computer Systems and Control at Technical University of Sofia, 8 Kl. Ohridski Blvd, Sofia 1000, Bulgaria, E-mail: <u>ivosim@abv.bg</u>

⁴Rumen Yordanov is with the Faculty of Electronic Engineering and Technologies at Technical University of Sofia, 8 Kl. Ohridski Blvd, Sofia 1000, Bulgaria, E-mail: <u>vordanov@tu-sofia.bg</u> with sampling frequency of 100Hz to minimize the integration errors. It is shown that the proposed system is capable to send the inertial and navigation data to database server in real-time situations and the navigation error may be reduced to increase the inertial navigation accuracy.

II. SYSTEM DESCRIPTION

The system block diagram is shown at Figure 1. It consists of the following main blocks used in the experiments:

- IMU system 9DoF system, consists of 3D linear accelerometer, 3D gyroscope and 3D magnetometer, which are integrated in the single IMU unit, produced by Atmel. One of the supported IMU systems is 9DoF Atmel Inertial One ATAVRSBIN1 board, which contains:
 - InvenSense three-axis MEMS gyroscope (ITG-3200)
 - Bosch Sensortec three-axis MEMS accelerometer (BMA150)
 - AKM three-axis electronic compass (AK8975)

• Temperature sensing through ITG-3200 or BMA150.

The second supported IMU system is Atmel Inertial Two ATAVRSBIN2 board which contains:

- InvenSense three-axis MEMS gyroscope (IMU-3000TM)
- Kionix® three-axis MEMS accelerometer (KXTF9)
- Honeywell three-axis electronic compass (HMC5883)
- Temperature sensing through IMU-3000.

The microcontroller read the data from the IMU system via CH0 channel of I^2C multiplexer.

- MEMS barometer based on the Atmel ATAVRSBPR1 board, which contains the high precision Bosch Sensortec digital pressure sensor (BMP085) with a temperature control and correction of the barometric data. The microcontroller read the data from the barometric board via CH1 channel of I²C multiplexer.
- I²C multiplexer based on PCA9540, which is 1-of-2 bidirectional translating multiplexer, controlled via the I²C bus. The SCL/SDA upstream pair fans out to two SCx/SDx downstream pairs or channels. The I²C multiplexer allows connecting two identical boards to the system expansion slots to increase the reliability for some critical applications such as unmanned devices.
- Micro SD card The additional flash memory up to 2GB is used to record the inertial, navigation, magnetic, temperature and barometric data. The microcontroller read/write the data from/to the micro SD card via SPI interface (MSSP1 module).
- GPS receiver The navigation data are obtained by the GPS/GNSS module (LEA 6S) produces by Swiss-based

å icest 2013

ublox. This module has been designed for low power consumption, low costs and UART, USB and DDC (I^2C compliant) interfaces. The GPS receiver is capable to update the navigation data up to 10Hz.

- GSM/GPRS modem is used to send the navigation and inertial data to the database server at a real-time. It is based on the quadband GSM (LEON G100) produced by the same company due to the simple integration of u-blox GPS and A-GPS and quad-band GSM/GPRS, class 10.
- Microcontroller The 8-bit high performance RISC PIC18 microcontroller is used to read the navigation and inertial data and to control the external devices according to their position. The PIC18 microcontrollers are optimized for C programming and have advanced peripherals (SPI/I²CTM, UARTs, PWMs, 10-bit ADC, etc.).



Figure 1. System block diagram

One of the system specific features is fastened with the I^2C multiplexer, so the reading algorithm had to be capable to switch between the both I^2C channels.

The data acquisition algorithm is shown at Figure 2. It consists of 10 frames with time duration of 10ms, so the 10 frames form 100ms duration data block. This data block contains of:

- ➤ NMEA 0183 RMC message (maximum 80 bytes);
- ▶ NMEA 0183 GGA message (maximum 80 bytes);
- 10 measurements of the 3-axis linear accelerometer (60 bytes);
- ➤ 10 measurements of the 3-axis gyroscope (60 bytes);
- 5 measurements of the 3-axis magnetometer (30 bytes) multiplexed with 5 temperature measurements from accelerometer and gyroscope (30 bytes);
- I barometer measurement and 1 temperature measurement of the barometer temperature for temperature corrections of the pressure.



Figure 2. Data acquisition algorithm

The data acquisition algorithm is agreed with the time conversion requirements of the barometer. The temperature measurement requires 4.5ms delay while the ultra high resolution pressure measurement – at least 25,5ms. The establishment of the corrected temperature and pressure data are accomplished on the basis of the barometer calibration EEPROM values and Bosch BMP085 Barometer Floating Point Pressure Calculations.

III. EXPERIMENTAL DATA AND ANALYSIS

An experimental test of the system is accomplished to test the ability of read, store and send the inertial and navigation data to the remote server. The data are recorded to the local system FLASH memory (micro SD card with capacity of 2GB) and after that the data are processed using MATLAB routine. The orientation of the IMU axes in relation to the vehicle axes is shown at Figure 3.



Figure 3. IMU axes orientation

The results are shown at the following figures:

Figure 4. X,Y,Z accelerometer data respectively;

Figure 5. Atmospheric pressure graph;

Figure 6. X,Y,Z gyroscope data respectively;

Figure 7. Altitude graph (GPS data);

Figure 8. X,Y,Z magnetometer data respectively;

Figure 9. Driving track (latitude/longitude)

å icest 2013





Figure 5. Barometer data





å icest 2013



Figure 8. X,Y,Z magnetometer data



Figure 9. Driving track

The shown graphic data proof the system ability to read all linear and angular accelerations, atmospheric pressure and GPS data and all chip temperature sensors (temperature graphs are not shown). The MEMS sensor information may be used for localization purposes when GPS signal is lost or is not available.

IV. CONCLUSIONS

The current paper discusses the 11DoF IMU system which is capable to all inertial and navigation data to solve the navigation tasks by combination of the IMU and GPS systems.

The design of this system is inspired by the need of a high speed IMU system which is capable to store locally and send data to remote server. The existing systems are distinguished with the first or second feature while the proposed system combines the both ones. The system may be used for inertial navigation based on the EKF (Extended Kalman filter) due to the high sampling frequency and small integration errors, gyro stabilized platforms, platform control due to the PWM interface, MVEDR (Motor Vehicle Event Data Recorder) systems or crash monitor for aircrafts, trains or cars.

ACKNOWLEDGEMENT

This paper was prepared and supported by the National Fund under contract number No.DTK02/2-2009.

REFERENCES

- [1]. Stephen Beeby, Graham Ensell, Michael Kraft, Neil White, MEMS Mechanical Sensors, Artech House, Ins, 2004
- [2]. Mohinder S. Grewal, Lawrence R. Weill, Angus P. Andrews, Global positioning systems, inertial navigation and integration, John Wiley & Sons., Inc., 2007
- [3]. Jussi Collin, G. Lachapelle, Jani Käppi, MEMS-IMU for Personal Positioning in a Vehicle – A Gyro-Free Approach, GPS 2002 Conference (Session C3a), Portland, OR, 24-27 September, U.S. Institute of Navigation
- [4]. www.st.com, AN3192, Application note, Using LSM303DLH for a tilt compensated electronic compass, Doc ID 17353 Rev 1, August 2010
- [5]. Pifu Zhang, Jason Gu, Evangelos E. Milios, and Peter Huynh, Navigation with IMU/GPS/Digital Compass with Unscented Kalman Filter, Proceedings of the IEEE International Conference on Mechatronics & Automation Niagara Falls, Canada, July 2005
- [6]. Luu Manh Ha, Tran Duc Tan, Chu Duc Trinh, Nguyen Thang Long, Nguyen Dinh Duc, INS/GPS Navigation for Land Applications via GSM/GPRS Network, Proceeding of 2nd Integrated Circuits and Devices in Vietnam (ICDV2011). ISBN: 978-4-88552-258-1, pp.30-55
- [7]. Salah Sukkarieh, Eduardo M. Nebot, and Hugh F. Durrant-Whyte, A High Integrity IMU/GPS Navigation Loop for Autonomous Land Vehicle Applications, IEEE TRANSACTIONS ON ROBOTICS AND AUTOMATION, Vol. 15, No. 3, June 1999